



ITEM	DESCRIPTION	MATERIAL	OTHER NOTES
A	FRAME	EXTRUDED ALUMINUM – ANODIZED CLEAR	BROKEN FRAME NOT AVAILABLE
B	BLADES	EXTRUDED ALUMINUM – ANODIZED CLEAR	INCLUDES 3100 SERIES (NON-INSULATED AIR FOIL) & 3900 SERIES (INSULATED)
C	ASSEMBLY SCREWS (FOR FRAME)	STAINLESS STEEL	---
D	BLADE SEALS	SANTOPRENE	SILICONE SEALS AVAILABLE UPON REQUEST
E	JAMB SEALS	SANTOPRENE	SILICONE SEALS AVAILABLE UPON REQUEST
F	OUTER BEARING	ULTRAFORM Q600	---
G	INNER BEARING	ULTRAFORM Q600	---
H	3/8" SQUARE BLADE AXLE	EXTRUDED ALUMINUM – ANODIZED CLEAR	---
I	LINKAGE CRANKARM	ZINC CASTING	---
J	BEARING	ULTRAFORM Q600	---
K	CLAMP BUSHING (SHORT)	STAINLESS STEEL	---
L	SOCKET HEAD CAP SCREW (SHORT)	STAINLESS STEEL	---
M	SOCKET HEAD CAP SCREW (LONG)	STAINLESS STEEL	---
N	Ø 5/16" LINKAGE ROD	STAINLESS STEEL	---
O	DRIVE SHAFT – 3/8" SQUARE AXLE	STAINLESS STEEL	---
P	CROSS BRACE	EXTRUDED ALUMINUM – ANODIZED CLEAR	INSTALLED WHEN SECTION HEIGHT GREATER THAN 36"
Q	OPPOSED BLADE LINKAGE JUMPER	ALUMINUM – ANODIZED CLEAR	REQUIRED ONLY FOR OPPOSED BLADE ACTION
R	CLAMP BUSHING (LONG)	STAINLESS STEEL	REQUIRED ONLY FOR OPPOSED BLADE ACTION