




LOUVERS & BACK DRAFT DAMPERS




2430 / 2435
4" DEEP DRAINABLE LOUVER



MODEL: 2430
FRAME: CHANNEL FRAME
DUCT-MOUNT (DM)



MODEL: 2435
FRAME: FLANGE FRAME
FLANGE-MOUNT (FM)



PERFORMANCE			
LOUVER UNIT SIZE	TOTAL AREA	FREE AREA	FREE AREA
48" x 48"	16 ft ²	9.06 ft ²	56.6%
(1219 x 1219 mm)	(1.49 m ²)	(0.84 m ²)	
BEGINNING POINT OF WATER PENETRATION AT 0.01 oz./ft ² FREE AREA:			896 FPM

STANDARD CONSTRUCTION	
DEPTH:	4" (102 mm)
MATERIAL:	EXTRUDED ALUMINUM - 6063-T5 ALLOY
FRAME THICKNESS:	0.081" (2.06 mm)
BLADE THICKNESS:	0.081" (2.06 mm)
BLADE ANGLE:	35°
BLADE CENTRES:	3.5" (89 mm)
BIRDSCREEN:	19 GA. GALVANIZED BIRDSCREEN - 1/2" x 1/2" OPENINGS
FINISH:	MILL

SIZE LIMITATIONS: SINGLE SECTION LOUVER		
	MINIMUM	MAXIMUM
WIDTH	12" (305 mm)	72" (1829 mm)
HEIGHT	12" (305 mm)	120" (3048 mm)
AREA	1 ft ² (0.09 m ²)	60 ft ² (5.57 m ²)

*LOUVER WILL BE MANUFACTURED 1/4" (6.4 mm) SMALLER (SINGLE SECTION) AND 1/2" (12.7 mm) SMALLER (MULTIPLE SECTION) THAN GIVEN OPENING DIMENSIONS UNLESS OTHERWISE SPECIFIED

AVAILABLE ACCESSORIES		
FINISH: <ul style="list-style-type: none"> BAKED ENAMEL FINISH DURANAR FINISH ANODIZED FINISH <ul style="list-style-type: none"> CLEAR ANODIZED LIGHT BRONZE MEDIUM BRONZE DARK BRONZE BLACK ANODIZED EXTENDED SILLS SECURITY BARS FILTER RACKS STAINLESS STEEL FASTENERS HINGED ACCESS DOORS ALL WELDED CONSTRUCTION CUSTOM GEOMETRIC SHAPES CONTINUOUS LINE CONSTRUCTION IS <i>NOT</i> RECOMMENDED* 	SCREENS: <ul style="list-style-type: none"> BIRDSCREEN <ul style="list-style-type: none"> 1/2" x 1/2" INTER CRIMPED ALUMINUM ALUMINUM BIRDSCREEN WITH FRAME INSECT SCREEN <ul style="list-style-type: none"> 18 x 14 MESH 	BLANK-OFF PANELS (ALUMINUM): VARIOUS GAUGES <ul style="list-style-type: none"> NON-INSULATED BLANK-OFF PANELS INSULATED BLANK-OFF PANELS <ul style="list-style-type: none"> 1" (25.4 mm) INSULATION 2" (50.8 mm) INSULATION

DWG. 2430 / 2435 JUNE 2020



LOUVERS & BACK DRAFT DAMPERS


2430 / 2435
4" DEEP DRAINABLE LOUVER

FREE AREA (Sq. Ft.)

		WIDTH (INCHES)															
		12	16	20	24	28	32	36	40	44	48	52	56	60	64	68	72
HEIGHT (INCHES)	12	0.32	0.45	0.58	0.72	0.85	0.98	1.11	1.24	1.38	1.51	1.64	1.77	1.90	2.03	2.17	2.30
	16	0.51	0.72	0.93	1.14	1.35	1.55	1.76	1.97	2.18	2.39	2.60	2.81	3.02	3.23	3.44	3.64
	20	0.70	0.98	1.27	1.56	1.84	2.13	2.42	2.70	2.99	3.28	3.56	3.85	4.14	4.42	4.71	4.99
	24	0.89	1.25	1.61	1.98	2.34	2.70	3.07	3.43	3.80	4.16	4.52	4.89	5.25	5.61	5.98	6.34
	28	1.07	1.52	1.96	2.40	2.84	3.28	3.72	4.16	4.60	5.04	5.48	5.92	6.37	6.81	7.25	7.69
	32	1.22	1.72	2.22	2.72	3.21	3.71	4.21	4.71	5.21	5.71	6.21	6.71	7.21	7.71	8.21	8.71
	36	1.41	1.98	2.56	3.14	3.71	4.29	4.87	5.44	6.02	6.60	7.17	7.75	8.33	8.90	9.48	10.06
	40	1.59	2.25	2.90	3.56	4.21	4.86	5.52	6.17	6.83	7.48	8.13	8.79	9.44	10.09	10.75	11.40
	44	1.78	2.51	3.24	3.98	4.71	5.44	6.17	6.90	7.63	8.36	9.09	9.83	10.56	11.29	12.02	12.75
	48	1.93	2.72	3.52	4.31	5.10	5.89	6.69	7.48	8.27	9.06	9.86	10.65	11.44	12.23	13.03	13.82
	52	2.12	3.00	3.87	4.74	5.61	6.48	7.35	8.23	9.10	9.97	10.84	11.71	12.58	13.46	14.33	15.20
	56	2.34	3.31	4.27	5.23	6.19	7.15	8.11	9.07	10.04	11.00	11.96	12.92	13.88	14.84	15.81	16.77
	60	2.49	3.51	4.53	5.55	6.58	7.60	8.62	9.64	10.66	11.68	12.71	13.73	14.75	15.77	16.79	17.81
	64	2.68	3.78	4.88	5.97	7.07	8.17	9.27	10.37	11.47	12.57	13.67	14.76	15.86	16.96	18.06	19.16
	68	2.87	4.04	5.22	6.40	7.57	8.75	9.92	11.10	12.28	13.45	14.63	15.80	16.98	18.16	19.33	20.51
	72	3.06	4.31	5.56	6.82	8.07	9.32	10.58	11.83	13.08	14.34	15.59	16.84	18.10	19.35	20.60	21.86
76	3.24	4.57	5.91	7.24	8.57	9.90	11.23	12.56	13.89	15.22	16.55	17.88	19.21	20.54	21.87	23.20	
80	3.43	4.84	6.25	7.66	9.07	10.48	11.88	13.29	14.70	16.11	17.52	18.93	20.34	21.74	23.15	24.56	
84	3.57	5.04	6.51	7.97	9.44	10.91	12.37	13.84	15.31	16.77	18.24	19.71	21.17	22.64	24.11	25.57	
88	3.76	5.31	6.85	8.39	9.94	11.48	13.03	14.57	16.11	17.66	19.20	20.74	22.29	23.83	25.38	26.92	
92	3.95	5.57	7.19	8.81	10.44	12.06	13.68	15.30	16.92	18.54	20.16	21.78	23.40	25.03	26.65	28.27	
96	4.14	5.84	7.54	9.23	10.93	12.63	14.33	16.03	17.73	19.42	21.12	22.82	24.52	26.22	27.92	29.61	
100	4.33	6.10	7.88	9.66	11.43	13.21	14.98	16.76	18.53	20.31	22.09	23.86	25.64	27.41	29.19	30.96	
104	4.52	6.37	8.22	10.08	11.93	13.78	15.64	17.49	19.34	21.20	23.05	24.90	26.76	28.61	30.46	32.32	
108	4.71	6.64	8.57	10.50	12.43	14.36	16.29	18.22	20.15	22.08	24.01	25.94	27.87	29.80	31.73	33.66	
112	5.08	7.17	9.25	11.34	13.42	15.51	17.59	19.68	21.76	23.85	25.93	28.02	30.10	32.19	34.27	36.35	
116	5.04	7.10	9.17	11.23	13.30	15.37	17.43	19.50	21.56	23.63	25.70	27.76	29.83	31.89	33.96	36.03	
120	5.17	7.29	9.41	11.53	13.65	15.77	17.89	20.01	22.13	24.25	26.37	28.49	30.61	32.73	34.85	36.97	

WATER PENETRATION - 2430 / 2435


15 MINUTE DURATION, TEST SIZE 48" X 48"



BEGINNING POINT OF WATER PENETRATION AT 0.01 oz/ft² FREE AREA IS 896 FPM

PRESSURE DROP 2430 / 2435

FIGURE 5.5 TEST SIZE 48" X 48"



*TEST RESULTS DO NOT INCLUDE THE EFFECTS OF BIRDSCREEN

DATA CORRECTED TO STANDARD AIR DENSITY @ 0.075 LBS/FT³.

RECOMMENDED SPECIFICATION

Furnish and install stationary louver models 2430 / 2435 as manufactured by Ventex Inc, Bolton, Ontario. Louvers must be licensed to bear the AMCA seal. Louvers shall be 4" (102 mm) deep. Blades shall be 0.081" (2.06 mm) extruded 6063-T5 aluminum alloy and frame shall be 0.081" (2.06 mm) extruded 6063-T5 aluminum alloy. Louvers shall have 19 gauge galvanized 1/2" x 1/2" birdscreen. All materials shall be factory finished after assembly with Polyester Power Coat in a color selected from the Ventex Color Chart.

CERTIFIED RATINGS

Ventex Inc. certifies that the models 2430 / 2435 shown here are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 511 and comply with the requirements of the AMCA Certified Ratings Program. The Certified Ratings Seal applies to air performance and water penetration ratings.



DWG. 2430 / 2435

JUNE 2020