



LOUVER QUICK SELECTION GUIDE

MODEL	DEPTH	BLADE TYPE / ANGLE	FREE AREA %	WATER PEN. (fpm)	MINIMUM SIZE	MAXIMUM SECTION SIZE
EXTRUDED ALUMINUM:						
2110	1-3/8"	STRAIGHT 30°	48.1	-	8" x 8"	60" x 60"
2210	2"	STRAIGHT 30°	53.2	478	12" x 8"	72" x 72"
2220	2"	STORM 45°	43.8	464	12" x 8"	72" x 72"
2410	4"	STRAIGHT 37°	53.3	627	12" x 12"	72" x 120"
2420	4"	STORM 45°	50.0	638	12" x 12"	72" x 120"
2430	4"	DRAINABLE 35°	56.6	896	12" x 12"	72" X 120"
2440	4"	SIGHT-PROOF 45°	45.1	573	12" X 8"	72" X 72"
2450	4"	H.P. STRAIGHT 35°	55.8	738	12" x 12"	72" x 120"
2590	5"	WIND-DRIVEN RAIN 40°	46.9	-	12" x 12"	60" x 120"
2620	6"	STORM 45°	50.4	705	16" x 16"	72" x 120"
2630	6"	DRAINABLE 40°	51.9	1100	16" x 16"	72" x 120"
2420-OP	4"	OPERABLE STORM 45°	42.6	-	16" x 16"	48" x 120"
2630-OP	6"	OPERABLE DRAINABLE 45°	-	-	16" x 16"	48" x 120"
FORMED STEEL / STAINLESS STEEL:						
2410S (-SS)	4"	STRAIGHT 45°	46.1	-	12" x 12"	40 SQ. FT.
2420S (-SS)	4"	STORM 45°	45.6	-	12" x 12"	40 SQ. FT.
2430S (-SS)	4"	DRAINABLE 37.5°	50.6	930	12" x 12"	40 SQ. FT.
ACOUSTICAL:						
ACL400	4"	STRAIGHT 45°	28.3	703	12" x 16"	60" x 96"
ACL600	6"	STRAIGHT 45°	27.5	704	12" x 16"	60" x 96"
ACL600F	6"	AIRFOIL 45°	37.6	703	12" x 16"	60" x 96"
ACL800	8"	STRAIGHT 45°	26.5	897	12" x 16"	60" x 96"
ACL800F	8"	AIRFOIL 45°	32.6	840	12" x 16"	60" x 96"
ACL1200	12"	STRAIGHT 45°	24.6	932	12" x 24"	60" x 72"
ACL1200F	12"	AIRFOIL 45°	31.8	1050	12" x 24"	60" x 72"
ACL1200V	12"	CHEVRON 45°	33.8	925	12" x 24"	60" x 72"