



Penthouses

Penthouses are available in both miter corner and mullion ER[ corner designV.

Available Louver Accessories

- Powder Coat Finish/Kynar 500 Finish/Anodizing
- Extended Sills
- Hinged Louver Doors
- Blank Off Panels/Insulated Blank Off Panels
- Insect Screen/Aluminum Bird Screens
- Specialty Shapes
- Filter Racks/Security Bars

6HUHV BackDraft Damper

The Ventex is a superior concept in back draft dampers. This unique all aluminum product eliminates the shortcomings of previous designs on the market. Pivot pins that quickly wear out or rust, rivets that shake loose and pull through the blade, are no longer a problem. The extruded aluminum blades are engineered to combine strength and durability with smooth operation by virtue of their aerodynamic design.

6HUHV Motorized Damper

The 9H[ is designed for exhaust or intake applications. The damper blade pivots in the middle, which makes it easier to open by balancing the positive and negative pressures on both sides of the blade. The advantage to the center pivot blade is the increased life expenctacncy of the motor. The design also gives the damper a high free area.



Alumavent Product Line Summary

3960/3965 Insulated (MSRL) Control Damper

Alumavent premium low leakage, extruded aluminum control damper features include thermally broken blades and optional frames. Santoprene vinyl, co-extruded blade and edge seals, provide less than 3 CFM per sq. ft. leakage @ 10"/tatic Sressure. The insulated construction helps prevent condensation build up and ensures the damper will not freeze.

3965ELT Extreme Low Temperature Insulated Control Damper

Alumavent 3965ELT Series Extreme Low Temperature insulated dampers feature thermally broken blades and frames as well as VSHFLDicone blade and jamb seals for maximum protection from the cold.

3160/3165 Airfoil (MSRL) Control Damper

The 316 features DLIRLOEODEBVM same high quality blade and jamb seals as the 3960 control damper. Available in opposed and parallel bladeFRD.

4000 Series (HDOHG) and 4100 Series (OHDNH) Steel Control DamperV

6tandard (V) triple V EODEcontrol damperV. The 4100 damper features stainless steel jamb seals and H[G vinyl blade sealsIRORZHDNDHDSSOLFDRQ.

2420OP/2425OP Operable Louver

The 2420-OP is an extruded aluminum louver that has movable blades. The operable louver features concealed linkage, vinyl blade edge seals, and stainless steel jamb seals in its standard construction. It is ideal for applications that do not have enough clearance for a stationary louver and motorized damper.

5100S (Static) and 5100D (Dynamic) Series 1-1/2 Hour Fire Dampers

Alumavent 5100S Series static fire dampers have a 1-1/2 Hour label and are suitable for use in HVAC systems where the fans shut down in the event of a fire alarm.

Alumavent 5100D Series dynamic fire dampers have a 1-1/2 Hour label and are tested and approved for use in HVAC systems where the fans remain on in the event of a fire alarm.

5100S-SS (DMF) Series Stainless Steel 1-1/2 Hour Static Fire Dampers

Alumavent 5100S-SS Series Stainless Steel fire dampers are excellent for use in high humidity and mildlycorrosive atmosphere applications. BLODEOHLZSHRVDLOHVVVWHO.

5300S (Static) and 5300D (Dynamic) Series 3 Hour Fire Dampers

Alumavent 5300S Series static fire dampers and 5300D Series dynamic fire dampers have a 3 Hour label suitable for use in fire separations with a fire resistance rating of 4 hours or less.

66 (DMF) 7KLOLER (DMF) LHDP SHV

7KH6HUHV7KLOLEDP SHVDHLBDOIRMHLQBLHDVGHSDVVRQZHHHDHODU  
ILHDP SHBDRVVKDEOH